DIMENSIONS & DATA CERTIFIED FOR:			
Representative: Order:			
Customer: Order:			
Project:			
Requirements:			
	By: Date:		
"A" (DIAMETER) 2-11/16[68] "B" (HEIGHT) 6[152] 6-15/16[1 "C" (FACE-TO-FACE) 3-1/2[89] 4[102] 3-1/2[89] 4["D" (BOTTOM TO ©) 5[127] 6[152] "E" (© TO OUTSIDE) 4-5/8[117] 4-13/16[122] 4-5/8[117] 4-13 "F" (© TO RETAINER) 3/4[19] 29/32[23] 3/4[19] 29/ BLOWDOWN CONN. (NPT) 1/4[6]	OPTIONS CONNECTIONS - NPT, BSPT OR SW LEFT-TO-RIGHT FLOW RIGHT-TO-LEFT FLOW BLOWDOWN VALVE		
Dimensions Are In Inches[mm]	NAME OF PART MATERIAL BODY, TRAP ASTM A167 T304L SS CONNECTOR BLOCK ASTM A351 GR. CF8 T304 SS SEAT, VALVE ASTM A582 T440F SS VALVE RETAINER, VALVE ASTM A167 T302 SS LEVER CARPENTER 20Cb-3 SS GUIDE PLATE ASSEMBLY ASTM A240 T304 SS BUCKET ASTM A167 T304 SS GASKET, CONNECTOR T304 SS NON-ASBESTOS RETAINING RING CARBON STEEL FLANGE ASTM A105 CARBON STEEL RETAINER, FLANGE ASTM A276 T304 SS SCREEN ASTM A167 T304 SS SCREEN ASTM A167 T304 SS GASKET, RETAINER ASTM A167 T3016 SS GASKET, RETAINER ASTM A167 T316 SS BOLTS ASTM A193, GR. B7 PLUG, PIPE CARBON STEEL		

2011 W/ 3/4" CONN. SHOWN

Three Rivers Division
Three Rivers, MI 49093
Armstrong (616) 273-1415 Fax(616) 278-6555
Posted on Armstrong's homepage www.armstrong-intl.com

rested on Amistrong's nomepage www.dimstrong intr.com			
Product	CD No.	Date	
TRAP		11/30/00	
2010-IS2	1113	Rev.	
2011-IS2			