

DIMENSIONS & DATA CERTIFIED FOR:

Representative:

Order:

Customer:


Order:

Project:


Requirements:

By:


Date:




MODEL WMT-1



MODEL WT-1



MODEL WT-2000



MODEL WT-3

MODEL NUMBER	WMT-1		WT-1		WT-2000	WT-3
Pipe Connections	1/4, 3/8	1/2	1/2	3/4	1/2, 3/4	1/2, 3/4
"A" (Diameter)	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
"B" (Height)	3-5/16	3-5/16	4-1/2	4-11/16	5-1/4	4-5/8
"C" (Face to Face)	—	—	—	—	2-3/8	—
"D" (Bottom to ϕ of Inlet/Outlet)	—	—	—	—	1"	—
Weight (lbs)	5 oz.	7 oz.	1	1-1/4	3-1/4	3
Maximum Allowable Pressure (Vessel Design)	250 psig at 400°F	250 psig at 400°F	400 psig at 650°F	400 psig at 650°F	400 psig at 650°F	600 psig at 750°F
Maximum Operating Pressure (psi)	250	250	400	400	400	600

Note: Dimensions are in inches

NAME OF PART	WMT-1	WT-1	WT-2000	WT-3
Body	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel	Carbon Steel, C-1018
Cap	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel	Carbon Steel, C-1018
Connections	304 Stainless Steel	304 Stainless Steel		—
Strainer Screen	—	.027" Perforated Stainless Steel	—	.027" Perforated Stainless Steel
Gasket	—	Stainless Steel Clad Non-asbestos	Stainless Steel Clad Non-asbestos	Stainless Steel Clad Non-asbestos
CAPSULE:				
Wafer	Hastelloy	Hastelloy	Hastelloy	Hastelloy
Body	304 Stainless Steel	303 Stainless Steel	303 Stainless Steel	303 Stainless Steel
Cap	304 Stainless Steel	303 Stainless Steel	303 Stainless Steel	303 Stainless Steel
Connector			304 Stainless Steel	—
Connector Gasket	—	—	Spiral Wound Stainless Steel Non-asbestos	—
Retaining Ring	—	—	Zinc Plated Carbon Steel	—
Connector Flange	—	—	Nickel Plated Carbon Steel	—
Flange Retainer	—	—	304 Stainless Steel	—



Armstrong International, Inc.
Three Rivers Division
Three Rivers, MI 49093
Armstrong (616) 273-1415 Fax (616) 278-6555

Product	CD No.	Date
THERMOSTATIC WAFER TRAPS	1017	11/09/94
		Rev. A